

MI DA2 002

2 channel actuator with DALI-2 input



- Relay module for direct control of loads via DALI-2
- Allows integration of power supplies without a DALI input into a DALI-2 system. Loads can be controlled via DALI-2 commands
- 2 potential-free outputs capable of controlling large loads (10 A)
- Powered by the DALI bus
- Compatible with DALI and DALI-2
- DIN rail format (1 ,module)
- DALI-2 Certified



Technical Characteristics

REFERENCE	MI DA2 002
Power source	Via DALI bus
Own consumption	4,5mA I _{typ} / 9,6mA I _{max}
Mounting	DIN rail
Output channels	2 x 10 A / 250V
Voltage free contact	yes
Type of connection terminal	Screw terminals
Cable section	<=2,5mm ²
Control	DALI-2
Dimensions	90 x 60 x 17,5 mm
Operating temperature	-5...45 °C
Storage temperature	-30...70 °C
Ingress Protection	IP20
Insulation class	Class II
Directives	Directive 2014/35/EU Directive 2014/30/EU Directive 2011/65/EU
Normatives	EN 60669-1, 2-1 / IEC 62386-101:2022 / IEC 62386-102:2022 / IEC 62386-103:2022 / IEC 62386-208:2009 / IEC 62386-301:2017

Dimensions



Installation

